



The Belden Catalog

Cable College

Corporate Information

Sales and Service

DISTRIBUTOR DESK

Copyright © 2003 Belden Inc.

[Cable finder](#)

[Technical Info](#)

[Conduit Capacity Chart](#)

[Connector Cross Ref.](#)

[Distributor Login](#)

[Help](#)

[Customer Service](#)

[Distributor Locator](#)

[Search Belden](#)

[Back](#) [New Search](#)

FULL TECHNICAL SPECS



8723 Paired - Audio, Control, and Instrumentation Cable

Total # Cond.		# Pairs				
4		2				
AWG	Stranding	Type	Insulation	Insulation Thickness (in.)	Shield	
22	(7x30)	TC - Tinned Copper	PP - Polypropylene	.00800	Individual Aluminum Foil-Polyester Tape	
Jacket	Jacket Thickness (in.)	Nom. OD (in.)	Nom. Cond. DCR (Ohms/M')	Nom. Imp. (Ohms)	Nom. Vel. of Prop. (%)	Nom. Cap. (pF/ft)
PVC - Polyvinyl Chloride	.0200	.1680	15.000	45.0	66.0	35.000

For technical data, click the button below

[Tech Data](#)

or call 1-800-BELDEN-1

For available colors, click the button below

[Put-ups & Colors](#)

or call 1-800-BELDEN-1

Description

Paired, 2 pairs, 22 AWG, stranded (7x30) TC - Tinned Copper conductors, PP - Polypropylene insulation, individual Aluminum Foil-Polyester Tape (Beldfoil) shielded pairs, 100% shield coverage, PVC - Polyvinyl Chloride jacket. Applicable Specifications: UL CM, CEC C(UL) CM. Flame Resistance: UL 1581 Vertical Tray. Pairs cabled on common axis with a 24 AWG stranded (7x32) tinned copper drain wire to reduce diameter. For Plenum versions, see 88723, 87723, 82723. BELDFOIL is a Belden registered trademark.

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors or omissions may occur. This listing of information is presented as a courtesy and does not ensure that a product with these specifications is available. Specification and availability should be confirmed with a call to our sales representative or to Customer Service. Have a question? Call us at 1-800-BELDEN-1 or send us a [comment](#)

04/14/03